

# Wiring, Printed - Component

**COMPANY**

**BASELECTRON SRL**

Via Mons. Angelini 18  
San Martino Siccomario, PV 27028 Italy

E146514

Type	Cond Width		SS/ DSO	Area Diam	Max date After	Report Surface Mount	2022- 01-01 Technology	Assembly		Max		Meets UL796	C T	I	
	Min mm	Cond Edge mm						SS/ DSO	Area Diam	date After	Surface Mount				2022- 01-01 Technology
<b>Multilayer printed wiring boards</b>															
<b>B</b>	0.08	0.08	16.5 Int:66	DS	50.8	No	-	-	-	275	10	125	V-0	All	*
<b>B1</b>	0.08	0.12	17 Int:34	DS	76.2	No	-	-	-	280	20	130	V-0	All	-
<b>B2</b>	0.075	0.1	17 Int:68	DS	50.8	No	-	-	-	288	10	130	V-0	All	*
<b>B4</b>	0.1	0.1	12 Int:68	DS	76.2	No	-	-	-	288	20	130	V-0	All	*
<b>B5</b>	0.12	0.2	17 Int:34	DS	50.8	No	-	-	-	280	10	130	V-0	All	-
<b>B6</b>	0.08	0.15	17 Int:68	DS	50.8	No	-	-	-	288	10	130	V-0	All	*
<b>B7</b>	0.12	0.2	17 Int:34	DS	50.8	No	-	-	-	280	10	130	V-0	All	-
<b>B8</b>	0.08	0.08	16.5 Int:66	DS	50.8	No	-	-	-	288	20	130	V-0	All	3
<b>B9</b>	0.1	0.1	17 Int:68	DS	25.4	No	-	-	-	288	20	130	V-0	All	*
<b>Single layer metal base printed wiring boards</b>															
<b>C</b>	0.18	0.54	35	SS	76.2	No	-	-	-	288	10	130	V-0	All	0
<b>C1</b>	0.08	0.08	35	SS	50.8	No	-	-	-	288	10	130	V-0	All	0
<b>C5</b>	0.15	0.21	34	SS	50.8	No	-	-	-	288	20	130	V-0	All	0

Single layer printed wiring boards															
<b>A</b>	0.08	0.08	16.5	DS	50.8	No	-	-	-	275	10	125	V-0	All	*
<b>A2</b>	0.075	0.1	17	DS	50.8	No	-	-	-	288	10	130	V-0	All	*
<b>A4</b>	0.1	0.1	12	DS	50.8	No	-	-	-	288	20	130	V-0	All	0
<b>A5</b>	0.12	0.2	17	DS	50.8	No	-	-	-	280	10	130	V-0	All	*
<b>A7</b>	0.12	0.2	17	DS	50.8	No	-	-	-	280	10	130	V-0	All	*
<b>A8</b>	0.08	0.08	16.5	DS	50.8	No	-	-	-	288	20	130	V-0	All	3
Singlelayer printed wiring boards															
<b>A9</b>	0.1	0.1	17	DS	25.4	No	-	-	-	288	20	130	V-0	All	*

\* - CTI marking is optional and may be marked on the printed wiring board.

DS - Duoble-Sided

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.

Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2023-06-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."