Product iQ®

Wiring, Printed Certified for Canada - Component

COMPANY
BASELECTRON SRL
Via Mons. Angelini 18
San Martino Siccomario, PV 27028 Italy

E146514

Type	Cond Width Min mm	Min Edge mm	Cond Thk mic	SS/ DS/ DSO	Max Area Diam mm	Report date After 2022-01-01	Surface Mount Technology	Assembly Solder Process Temp °C	Assembly Solder Process Cycles	Solder Limits °C	Solder Limits sec	Max Oper Temp °C	Flame Class	Meets UL796 DSR	C T I
Metal Base Single Layer Printed Wiring Boards															
F001	0.13	0.13	17	SS	25.4	No	-	-	-	270	10	130	V-0	All	*
F002	0.1	0.3	17	SS	50.8	No	-	-	-	270	10	130	V-0	All	0
Multilayer printed wiring boards															
B	0.08	0.08	16.5 Int:66	DS	50.8	No	-	-	-	275	10	125	V-0	All	*
B2	0.075	0.1	17 Int:68	DS	50.8	No	-	-	-	288	10	130	V-0	All	*
B5	0.12	0.2	17 Int:34	DS	50.8	No	-	-	-	280	10	130	V-0	All	-
B7	0.12	0.2	17 Int:34	DS	50.8	No	-	-	-	280	10	130	V-0	All	-
B8	0.08	0.08	16.5 Int:66	DS	50.8	No	-	-	-	288	20	130	V-0	All	3
B9	0.1	0.1	17 Int:68	DS	25.4	No	-	-	-	288	20	130	V-0	All	*
F011	0.17	0.35	17 Int:34	DS	50.8	No	-	-	-	288	20	130	V-0	All	*
F012	0.17	0.35	17 Int:34	DS	25.4	No	-	-	-	288	20	130	V-0	All	*
F013	0.07	0.07	17 Int:102	DS	25.4	No	-	-	-	288	20	130	V-0	All	*
F026	0.1	0.1	17 Int:68	DS	50.8	No	-	-	-	288	20	130	V-0	All	*
Single layer metal base printed wiring boards															
C	0.18	0.54	35	SS	76.2	No	-	-	-	288	10	130	V-0	All	0
C1	0.08	0.08	35	SS	50.8	No	-	-	-	288	10	130	V-0	All	0
C5	0.15	0.21	34	SS	50.8	No	-	-	-	288	20	130	V-0	All	0
F005	0.10	0.10	6	SS	50.8	Yes	Yes	260	3	-	-	105	V-0	All	2

F006	0.09	0.09	17	SS	50.8	No	-	-	-	288	20	90	V-0	All	0
Single layer printed wiring boards															
A	0.08	0.08	16.5	DS	50.8	No	-	-	-	275	10	125	V-0	All	*
A2	0.075	0.1	17	DS	50.8	No	-	-	-	288	10	130	V-0	All	*
A5	0.12	0.2	17	DS	50.8	No	-	-	-	280	10	130	V-0	All	*
A7	0.12	0.2	17	DS	50.8	No	-	-	-	280	10	130	V-0	All	*
A8	0.08	0.08	16.5	DS	50.8	No	-	-	-	288	20	130	V-0	All	3
F014	0.12	0.23	17	DS	50.8	No	-	-	-	288	20	130	V-0	All	*
F015	0.12	0.23	17	DS	50.8	No	-	-	-	274	20	130	V-0	All	*
F016	0.07	0.07	17	DS	50.8	No	-	-	-	288	20	130	V-0	All	*
F017	0.07	0.07	17	DS	38.1	No	-	-	-	288	20	130	V-0	All	*
F018	0.273	0.819	34	DS	13.0	No	-	-	-	260	10	105	V-1	▲	*
F019	0.273	0.819	34	SS	13.0	No	-	-	-	260	10	105	V-1	All	*
F028	0.1	0.1	17	DS	50.8	No	-	-	-	288	20	130	V-0	All	*
Singlelayer printed wiring boards															
A9	0.1	0.1	17	DS	25.4	No	-	-	-	288	20	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

DS - Duoble-Sided

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.

Marking: Company name or trademark  or file number and type designation and the Recognized Component Mark for Canada, . May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2026-09-02

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."