

**ZPXK2.E477015****Wiring, Printed - Flexible Material Constructions - Component**

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Flexible Material Constructions - Component

[See General Information for Wiring, Printed - Flexible Material Constructions - Component](#)

BASELECTRON SRL

E477015

VIA MONS. ANGELINI 22/A

27028 S MARTINO SICCOMARIO, PV ITALY

	Cond Width		Cond	SS/ DS/ DSO	Max	Solder	Oper	Max	Meets	C	
	Min	Edge			Area			Temp			Flame
Type	mm(in)	mm(in)	Thk mic(mil)	DSO	Diam mm(in)	C	sec	C	Class	DSR	I
Multilayer flexible materials interconnect constructions (Flexible Application).											
FM	0,09 (0,004)	0,09 (0,004)	12 (0,47) Int:35	DS	50,8 (2,0)	288	20	105	V-0	-	-
Multilayer Rigid Flex Composite, Flexible Materials Interconnect Constructions (Flexible Application).											
RF	0,09 (0,004)	0,09 (0,004)	35 (1,38) Int:35	DS	50,8 (2,0)	288	10	120	V-0	-	-
Single layer flexible materials interconnect constructions(Flexible Application).											
F	0,09 (0,004)	0,09 (0,004)	12 (0,47)	DS	50,8 (2,0)	288	20	105	V-0	-	-

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2015-06-24

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".